

## DS-2TS03-35UM/W

### Handheld Observational Thermal Monocular



Hikvision DS-2TS03 handheld observational thermal monocular is equipped with a 384×288 infrared detector and a 1024×768 OLED display. It supports functions of observation, hot spot tracking, distance measurement, Wi-Fi hot spot, and so on. The high-sensitivity built-in thermal detector provides you with clear view even in total darkness.

#### Key Features

- 384 × 288 resolution, high sensitivity detector
- DDE (Digital Detail Enhancement) technique
- 3D DNR, adaptive AGC (Automatic Gain Control)
- 1024 × 768 resolution 0.39-inch OLED display
- Built-in rechargeable Li-ion battery
- Up to five hours continuous running (with GPS function and Wi-Fi hot spot function off)
- Small in size and light in weight



## Application Scenarios


The monocular is mainly applied to scenarios such as patrolling, law enforcement, searching and rescuing, drug enforcement, anti-smuggling, criminal seizing, hiking, travel, and hunting, etc.,




Security checking



Patrolling



Searching and rescuing



Criminal seizing



Avoid beasts



Hunting

## Functions

### Distance Measurement:

The device realizes distance measurement function after marking the top and bottom of target, and input the target height.

### Hot Spot Mark:

The device detects and marks the hot spot of highest temperature.

### Wi-Fi Hot Spot:

Device can capture snapshots, record videos, and set parameters via APP after being connected to your phone.

### GPS Function:

The device can be located with GPS system.

### Storage:

Built-in memory module supports video recording/snapshot capturing.

### Digital Zoom:

Device supports 2× digital zoom.

## Specifications

		Model	DS-2TS03-35UM/W
Parameter		Handheld Observational Thermal Monocular	
Thermal Module	Image sensor	Uncooled Focal Plane Arrays	
	Max. Resolution	384 × 288	
	Response waveband	8μm to 14μm	
	NETD	< 40mk (@25°C, F#=1.0)	
	Lens (focal length)	35mm, Manual Focus	
	MRAD	0.49	
	Field of View	10.66° × 8°	
	F number	1.0	
Image Display	Monitor	0.39-inch, OLED, 1024 × 768	
	Palettes	Black hot White hot Red hot	
System	Hot Track	Support	
	WIFI	Support	
	Storage	Built-in memory module (16GB)	
	Digital Zoom	2×	
	Capture Snapshot	Support	
	Record Video	Support on-board video / image recording	
	GPS	Support	
Power Supply	Battery Type	Lithium Battery	
	Battery Operating Time	Up to five hours continuous running (with GPS function and Wi-Fi hot spot function off)	
	Battery Capacity Display	Support	
General	Power	5V DC/2A, 2W	
	Working Temperature	-30 °C to 55 °C (-22 °F to 131 °F)	
	Protection level	IP67	
	Drop Test Height	2 m (6.56 feet)	
	Dimension (L x W x H)	202 mm × 74 mm × 66 mm (7.95 " × 2.91 " × 2.60 ")	
	Weight	500 g (1.1 lb)	

## Wide Range Coverage for Different Specifications


**Note:** The table below is only for reference, the performance varies from model to model, and the specific data is based on 17 μm pixel space-between.

Detection Range (Vehicles: 1.4×4.0m)	Detection Range (Humans: 1.8×0.5m)	Recognition Range (Vehicles: 1.4×4.0m)	Recognition Range (Humans: 1.8×0.5m)	Identification Range (Vehicles: 1.4×4.0m)	Identification Range (Humans: 1.8×0.5m)
3157m	1029m	789m	257m	395m	129m

## Order Models

DS-2TS03-35UM/W

## Dimensions



Distributed by



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com

0100001080831