

DS-K1102M/MK

Card Reader



DS-K1102M Mifare Card Reader
DS-K1102MK Mifare Card Reader with Keypad

-
- PC+ABS material shell with PMMA panel design and alloy decoration;
 - Equipped with the 32-bit high-speed processor;
 - Built-in audible beeper;
 - Display the reader status with LED indicator;
 - DIP switch;
 - RS485 and Wiegand(W26/W34) protocol;
 - Tamper-proof alarm;
 - Online upgrade function (under the 485 communication mode). Card reader can degrade to pre-upgrade status in case of upgrading failed;
 - Watchdog design for repairing itself in case that exception occurs, to ensure the longservice life of the reader;
 - Dust-proof and water-proof design;
 - Read Mifare card and obtain the card No.;



Model	DS-K1102M/MK
Power Supply	12V DC
Working Current	≤500mA
Processor	32-bit
Reading Frequency	13.56MHz
Reading Range	30 to 50mm (1.18 to 1.96")
ID Settings	Setting by the DIP Switch on the Main Board
Audio Alert	Beeper
Power Consumption	≤6W
Keypad	No Keypad (DS-K1102M) Keypad with 12 Keys (0 to 9, *, #) (DS-K1102MK)
Certifications	FCC, CE
LED Indicator	Power Indicator; Status LED Indicator
Working Temperature	-40°C to +70°C (-40°F to +158°F)
Working Humidity	10% to 90% (Non Condensing)
Protection Level	IP 64
Dimensions	121×86.5×14mm (4.76×3.41×0.55")
Weight	≤ 0.14Kg
Installing Method	Applied for 86 & 120 Gang Box