

DS-PDQP15AM-LM-WE Wireless 180° Panoramic Detector

Wireless 180° Panoramic Detector is a two-way wireless outdoor quad PIR detector with 180° lens coverage. This device is designed to protect the outdoor areas of your property and especially suitable for large free space applications.

- 180° panoramic coverage
- Active IR anti-masking
- IP65 weather resistance for outdoor application
- Multiple enrollment methods and easy installation
- Frequency hopping against jamming for reliable transmission



Specification

Detection Performance	Detection Performance			
Detection Method	Passive infrared			
Sensor Model	SFG323-711			
Detection Range	15 m			
Detection Angle	180°			
Detection Zones	40			
Detectable Speed	0.3 to 2m/s			
Sensitivity	Auto,Low			
White Light Filter	20000lux			
Pet Immunity	Up to 40 kg (cm height)			
Digital Temperature	Support			
Compensation	Support			
Anti-masking	Support			
Adaptable Coverage	Pattern mask included			
Feature				
Digital Processing	Support			
Sealed Optics	Support			
Tamper Protection	Front, rear			
Environment Temperature	Support			
Indicator	Support			
Signal Strength Indicator	Support			
Interface				
Power Switch	Power up enrolling			
LED Indicator	Blue(alarm), green+orange(mask)			
Transmission				
Transmission Technology	Tri-X Wireless			
Transmission Method	Two-Way RF wireless			
Transmission Frequency	868 MHz			
Transmission Security	AES-128 encryption			
Transmission Range(Free Space)	1.6 km			
Frequency Hopping	Support			
Enrolling Method	Power up, remote ID, QR code			
Electrical Characteristics				
Standard Battery Life	Up to 5 years (standby time) (The battery working time can be significantly reduced at			
Standard Battery Life	low temperatures)			
Power Supply	Battery powered			
Battery Type	CR123A × 5			
Typical Voltage	3V			
General				
Operation Temperature	-25°C to 60°C (-13°F to 140°F)			
Storage Temperature	-25°C to 60°C (-13°F to 140°F)			
Operation Humidity	10% to 90%			
IP Rate	IP65			



•

Dimension(WxHxD)	75 mm × 202 mm × 73 mm
Weight	512.5 g
Mounting Height	0.8 m to 1.2 m
Mounting Method	Wall
Application Scenario	Outdoor

Available Model

DS-PDQP15AM-LM-WE

Accessory

Optional

DS-PDP-IN-CR123A Indoor Detector	DS-PDP-EX-BATT	DS-PDCM15PF-IR
Battery		
Linburn Barnay Littico, + CR123A 3.0V -		



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.











Hikvision Corporate Channel



©Hikvision Digital Technology Co., Ltd. 2023 | Data subject to change without notice |