

STELLAR SH50**Thermal Image Scope**

HIKMICRO STELLAR SH50 Thermal Image Scope has 384*288 thermal detector and 1024*768 OLED display, which provides clear image under harsh environment conditions like darkness, fog, smoke, dust, rain, snow, wood, camouflage, etc. The traditional-style 50mm Tube meets the needs of professional hunters who value traditions and seek technological superiority, ensure an extreme detection range of up to 2600 meters

Key Features

- 384*288 thermal resolution, high sensitivity detector, NETD < 35 mK (25°C, F# = 1.0)
- Supports audio recording
- Supports recoil-activation recording
- Supports video recording and snapshot, built-in EMMC (64 GB)
- 1024*768 resolution 0.39-inch OLED display
- Observation Distance up to 2600 m

Specification

Thermal Module

Image Sensor	Uncooled Focal Plane Array
Max. Resolution	384 × 288
Frame Rate	50 Hz
Pixel Interval	12 μm
Response Waveband	8 μm to 14 μm
NETD	< 35 mK (25°C, F# = 1.0)
Lens (Focal Length)	50 mm
Detection Range	2600 m
Field of View	5.28° × 3.96°
Min. Focusing Distance	5 m
Aperture	F1.0
Magnification	3.85×

Image Display

Display	1024 × 768, 0.39 inch, OLED
Image Mode	Black Hot, White Hot, Red Hot, Fusion
FFC (Flat Field Correction) Mode	Auto, Manual, External Correction
Exit Pupil	5 mm
Eye Relief	60 mm
Diopter (Range)	-5 D to 5 D

System

Digital Zoom	1×, 2×, 4×, 8×
Capture Snapshot	Yes
Record Video	On-board video recording
Standby Mode	Yes
Storage	Built-in EMMC (64 GB)
PIP	Yes
DPC	Yes
Hotspot	Yes
Uniformity Correction	Auto, Manual, External Correction
Hot Track	Yes
Reticle	Yes
Audio Recording	Yes
Recoil-activation Recording	Yes
Max. Recoil	1000g

Power Supply

Battery Type	Two rechargeable Lithium batteries (internal) and one replaceable CR123A (external)
Battery Operating Time	15 hours continuous running (@25°C, Wi-Fi off)
Battery Capacity Display	Yes
Anti-reverse Battery Connection	Yes
Overvoltage Protection	Yes
Power Supply	5 V DC/2 A, USB Type-C interface Supports QC3.0



General

Work Temperature	-30°C to 55°C (-22°F to 131°F)
Protection Level	IP67
Dimension	420mm × 78.1 mm × 82 mm
Weight	970 g without eyepiece and CR123A

Available Model


SH50

Dimension



Unit: mm


Accessory




Quick Start Guide (x1)



Battery CR123A (x1)



Type-C Cable (x1)



Dust-free Cloth (x1)



Bag (x1)

COMPLIANCE NOTICE: The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries.

