

Gigabit Ethernet Switch

WI-SG324F

Overview

Wi-Tek Gigabit Ethernet Switches provide an easy way to expand your wired network. With all ports support Auto-MDI/MDIX, there's no need to worry about the type of cable to use. Featuring full duplex mode can send and receive data at a rate up to 1000Mbps, making it an ideal choice for expanding your high performance network.

Features

Full gigabit access, full-line speed forwarding

All ports support high-speed forwarding, user-flexibly flexible networking, to meet the needs of various scenarios networking, such as hotel, campus, factory dormitory and small and medium-sized enterprises.

Plug and play, no configuration required

A plug-and-play design lets administrators quickly connect the switch to devices with no hassles, no technician needed. Auto-negotiation on each port senses and adjusts the link speed of a network intelligently to ensure an overall boost in performance and reliability. Convenient for wall-mounted, desktop and rack installations.

Long service Life with sturdy and durable metal shell

Wi-Tek Gigabit Ethernet Switches are protected by high-quality metal shell to ensure the long service life. They have passed a series of strict tests and provided you with reliable performance.

Environmentally friendly with your Ethernet

Wi-Tek Gigabit Ethernet Switches make use of innovative energy-saving technologies. Power consumption automatically adjusts according to link status and cable length.



Specifications



HARDWARE FEATURES	WI-SG324F
Hardware Version	
Standards	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1p
Interface	8 10/100/1000Mbps RJ45 Ports 16 1000Mbps SFP Slots
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e, 6 or above cable (maximum 100m) 1000BASE-X: MMF, SMF 1000Base-L X:62.5µm/50µm MM(2m~550m) or 10µm SMF(2m~5000m)
LED Indicator	PoE/Link/Power
Fan Quantity	Fanless
Exchange Capacity	52G
Packet Forwarding Rate	38.69Mpps
Mac Address Table	8K
Power Adapter	AC IN : 110~240V
Packet Buffer Memory	12Mb
Jumbo Frame	10240Bytes
Port VLAN	No
OTHERS	
Certification	CE, FCC, RoHS
Package Dimension	515×300×95mm
Switch Dimension	440×220×45mm
Gross Weight	3.28kg
Net Weight	2.45kg
Package Contents	1 × Switch 1 × Power Cord 1 × Rack-mount Kit 1 × Rubber Feet 1 × Quick Installation Guide
Working Temperature	-10°C~55°C
Storage Temperature	-40°C~70°C
Working Humidity	10%~90% RH non-condensing
Storage Humidity	5%~90% RH non-condensing



Wireless-Tek Technology Limited
Address: Building 3, Units 1801-1807, 1812, Huaqiang Era Plaza, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen City, Guangdong Province, China.
Website: www.wireless-tek.com
Tel: 86-0755-32811290
Email: sales@wireless-tek.com
Technical Support: tech@wireless-tek.com



Technical Support



Cloud Management



Company Website