



# 2019

## Q3 CORE PRODUCT QUICK GUIDE



## DEALER PARTNER PROGRAM

### CAPITALISING PROJECT OPPORTUNITIES



\* For further informations, please contact your distributor

# CONTENTS

---

IP Cameras .....	2
Turbo HD Cameras .....	9
IP PTZ Cameras .....	13
Turbo HD PTZ Cameras .....	14
Thermal Security .....	15
Thermography .....	17
Commercial Vision .....	17
Network Video Recorders .....	18
DVRs .....	20
Controller .....	22
Terminals .....	23
Readers & Keypads .....	23
Video Intercom Kit .....	24
IP Door Stations .....	25
IP Indoor Stations .....	26
Hikvision Intrusion Alarm .....	26
Alarm Kit .....	27
Hikvision Wireless Dual-Tech Detector .....	27
Displays .....	28
Switches .....	29

# IP CAMERAS

**DS-2CD2025FWD-I**  
2MP IR Fixed Bullet Network Camera



- Up to 2MP resolution
- H.265+
- Powered by Darkfighter
- Min.illumination: 0.005Lux
- 120dB WDR
- IP67

**PART NO.**  
DS-2CD2025FWD-I(2.8mm)

**DS-2CD204360-I**  
4 MP IR Fixed Bullet Network Camera



- Up to 4MP resolution
- Min. illumination: 0.01 Lux
- H.265+
- 120dB WDR
- IP67

**PART NO.**  
DS-2CD204360-I(2.8mm)

**DS-2CD2045FWD-I**  
4 MP IR Fixed Bullet Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination:0.009 lux
- H.265+
- 120dB WDR
- IP67

**PART NO.**  
DS-2CD2045FWD-I(2.8mm)

**DS-2CD2045FWD-I(BLACK)**  
4 MP IR Fixed Bullet Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination : 0.009 lux
- H.265+
- 120dB WDR
- IP67

**PART NO.**  
DS-2CD2045FWD-I(BLACK)(2.8mm)

**DS-2CD2085FWD-I(B)**  
8MP Mini Bullet Network Camera



- Up to 8MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.008Lux
- 120dB WDR
- IP67

**PART NO.**  
DS-2CD2085FWD-I(B)(2.8mm)

**DS-2CD2125FWD-I(S)**  
2 MP Ultra-Low Light Network Dome Camera



- Up to 2MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.005Lux
- 120dB WDR
- IP67,IK10

**PART NO.**  
DS-2CD2125FWD-I(2.8mm)  
DS-2CD2125FWD-I(4mm)  
DS-2CD2125FWD-IS(2.8mm)

## DS-2CD214360-I

4 MP IR Fixed Dome Network Camera



- Up to 4MP resolution
- Min. illumination: 0.01 Lux
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD214360-I(2.8mm)

## DS-2CD2145FWD-IS

4 MP IR Fixed Dome Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination: 0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2145FWD-I(2.8mm)

## DS-2CD2145FWD-IS(BLACK)

4 MP IR Fixed Dome Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination : 0.009 lux
- H.265+
- 120dB WDR
- IP67,IK10

### PART NO.

DS-2CD2145FWD-I(BLACK)(2.8mm)

## DS-2CD214661-I(S)

4 MP IR Fixed Dome Network Camera



- Up to 4MP resolution
- H.265
- 120dB WDR
- Powered by DarkFighter
- Min. illumination : 0.007 Lux
- AcuSense, False alarm filter by target classification
- IR range: Up to 30 m
- IP67, IK10

### PART NO.

DS-2CD214661-I(2.8mm)

## DS-2CD218360-I

8 MP IR Fixed Dome Network Camera



- Up to 8MP resolution
- Min. illumination: 0.01 lux
- H.265+
- 120dB WDR
- IP67,IK10

### PART NO.

DS-2CD218360-I(2.8mm)

## DS-2CD2325FWD-I

2MP Ultra-Low Light Network Turret Camera



- Up to 2MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.005Lux
- 120dB WDR
- IP67

### PART NO.

DS-2CD2325FWD-I(2.8mm)

# IP CAMERAS

## DS-2CD234360-I

4 MP IR Fixed Turret Network Camera



- Up to 4MP resolution
- Min. illumination: 0.01 Lux
- H.265+
- 120dB WDR
- IP67

### PART NO.

DS-2CD234360-I(2.8mm)

DS-2CD234360-I(4mm)

## DS-2CD2345FWD-I

4 MP IR Fixed Turret Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination:0.009 lux
- H.265+
- 120dB WDR
- IP67

### PART NO.

DS-2CD2345FWD-I(2.8mm)

## DS-2CD2345FWD-I(BLACK)

4 MP IR Fixed Turret Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination : 0.009 lux
- H.265+
- 120dB WDR
- IP67

### PART NO.

DS-2CD2345FWD-I(BLACK)(2.8mm)

## DS-2CD2346G1-I

4 MP IR Fixed Turret Network Camera



- Up to 4MP resolution
- H.265
- 120dB WDR
- Powered by DarkFighter
- Min. illumination : 0.007 Lux
- AcuSense, False alarm filter by target classification
- IR range: Up to 50 m
- IP67

### PART NO.

DS-2CD2346G1-I(2.8mm)

## DS-2CD2385FWD-I(B)

8MP Network Turret Camera



- Up to 8MP resolution
- H.265+
- Min.illumination: 0.01Lux
- 120dB WDR
- IP67

### PART NO.

DS-2CD2385FWD-I(2.8mm)

DS-2CD2385FWD-I(B)(2.8mm)

## DS-2CD244360-I(W)

4 MP IR Fixed Cube Network Camera



- Up to 4MP resolution
- Min. illumination:0.01 Lux
- H.265+
- 120dB WDR
- IR: up to 10 m
- PIR: 10 m
- Wi-Fi (Optional)

### PART NO.

DS-2CD244360-IW(2.8mm)(PSU)

## DS-2CD2525FWD-I(W)(S)

2 MP EXIR Fixed Mini Dome Network Camera



- Up to 2MP resolution
- IR: Up to 10 m
- H.265+
- 120dB WDR
- Wi-Fi (-W)

### PART NO.

DS-2CD2525FWD-IS(2.8mm)

## DS-2CD254360-IS

4 MP EXIR Fixed Mini Dome Network Camera



- Up to 4MP resolution
- IR: Up to 10 m
- H.265+
- 120dB WDR
- Wi-Fi (Optional)

### PART NO.

DS-2CD254360-I(2.8mm)

DS-2CD254360-IS(2.8mm)

## DS-2CD2625FWD-IZS

2MP WDR Vari-focal Network Bullet Camera



- Up to 2MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.005Lux
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2625FWD-IZS(2.8-12mm)

## DS-2CD2625FWD-IZS(BLACK)

2MP WDR Vari-focal Network Bullet Camera



- Up to 2MP resolution
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2625FWD-IZS(BLACK)

## DS-2CD2645FWD-IZS

4 MP IR VF Bullet Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination:0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2645FWD-IZS(2.8-12mm)

## DS-2CD2645FWD-IZS(BLACK)

4 MP IR VF Bullet Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min.illumination: 0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2645FWD-IZS(BLACK)(2.8-12mm)

# IP CAMERAS

## DS-2CD2646G1-IZ(S)

AcuSense 4 MP IR Varifocal Bullet Network Camera



- Up to 4MP resolution
- Max. 2688 × 1520 @ 30fps
- H.265
- 120dB WDR
- Powered by DarkFighter
- Min. illumination: 0.007 Lux
- AcuSense, False alarm filter by target classification
- IR range: Up to 50 m
- IP67, IK10

### PART NO.

DS-2CD2646G1-IZS(2.8-12mm)

## DS-2CD2685FWD-IZS(B)

8MP WDR Vari-focal Network Bullet Camera



- Up to 8MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.008Lux
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2685FWD-IZS(2.8-12mm)(B)

## DS-2CD2685FWD-IZS(BLACK)

8MP WDR Vari-focal Network Bullet Camera



- Up to 8MP resolution
- H.265, H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2685FWD-IZS(BLACK)

## DS-2CD2725FWD-IZS

2MP WDR Vari-focal Network Dome Camera



- Up to 2MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.005Lux
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2725FWD-IZS(2.8-12mm)

## DS-2CD2725FWD-IZS(BLACK)

2MP WDR Vari-focal Network Dome Camera



- Up to 2MP resolution
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2725FWD-IZS(BLACK)

## DS-2CD2745FWD-IZS(B)

4 MP IR VF Dome Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min.illumination: 0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

### PART NO.

DS-2CD2745FWD-IZS(2.8-12mm)(B)



**DS-2CD2745FWD-IZS(BLACK)**  
4 MP IR VF Dome Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min.illumination: 0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

**PART NO.**

DS-2CD2745FWD-IZS(BLACK)(2.8-12mm)

**DS-2CD2746G1-IZ(S)**  
AcuSense 4 MP IR Varifocal Dome Network Camera



- Up to 4MP resolution
- H.265
- 120dB WDR
- Powered by DarkFighter
- Min. illumination: 0.007 Lux
- AcuSense, False alarm filter by target classification
- IR range: Up to 30 m
- IP67, IK10

**PART NO.**

DS-2CD2746G1-IZS(2.8-12mm)

**DS-2CD2785FWD-IZS(B)**  
8MP WDR Vari-focal Network Dome Camera



- Up to 8MP resolution
- H.265+
- Powered by DarkFighter
- Min.illumination: 0.008Lux
- 120dB WDR
- IP67, IK10

**PART NO.**

DS-2CD2785FWD-IZS(2.8-12mm)(B)

**DS-2CD2H45FWD-IZS(B)**  
4 MP IR VF Turret Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min.illumination: 0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

**PART NO.**

DS-2CD2H45FWD-IZS(2.8-12mm) (B)

**DS-2CD2H45FWD-IZS(BLACK)**  
4 MP IR VF Turret Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min.illumination : 0.009 lux
- H.265+
- 120dB WDR
- IP67, IK10

**PART NO.**

DS-2CD2H45FWD-IZS(BLACK)(2.8-12mm)

**DS-2CD2T25FWD-I5/I8**  
2 MP IR Fixed Bullet Network Camera



- Up to 2MP resolution
- Powered by DarkFighter
- Min. illumination: 0.005 Lux
- H.265+
- 120dB WDR
- IR range: 50m, 80m, optional
- IP67

**PART NO.**

DS-2CD2T25FWD-I5(2.8mm)

# IP CAMERAS

---

## DS-2CD2T4360-I5/I8

4 MP IR Fixed Bullet Network Camera



- Up to 4MP resolution
- Min. illumination: 0.01 Lux
- H.265+
- 120dB WDR
- IP67

---

### PART NO.

DS-2CD2T4360-I5(2.8mm)

---

DS-2CD2T4360-I5(4mm)

---

DS-2CD2T4360-I8(4mm)

---

## DS-2CD2T45FWD-I5/I8

4 MP IR Fixed Bullet Network Camera



- Up to 4MP resolution
- Powered by DarkFighter
- Min. illumination: 0.009 lux
- H.265+
- 120dB WDR
- IP67

---

### PART NO.

DS-2CD2T45FWD-I5(2.8mm)

---

## DS-2CD2T46G1-2I/4I

4 MP IR Fixed Bullet Network Camera



- Up to 4MP resolution
- H.265
- 120dB WDR
- Powered by DarkFighter
- Min. illumination : 0.007 Lux
- AcuSense, False alarm filter by target classification
- IR range: Up to 50/80 m
- IP67

---

### PART NO.

DS-2CD2T46G1-4I(2.8mm)

---

## DS-2CD2T85FWD-I5/I8(B)

8 MP IR Fixed Bullet Network Camera



- Up to 8MP resolution
- H.265+
- Min. illumination: 0.01Lux
- 120dB WDR
- IP67

---

### PART NO.

DS-2CD2T85FWD-I8(B)(4mm)

# TURBO HD CAMERAS

## DS-2CE10DFT-F

2 MP Full Time Color Bullet Camera



- 2 MP
- Full time color
- 3.6 mm, 6 mm fixed lens
- Up to 20 m white light distance
- true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE10DFT-F(3.6mm)

## DS-2CE10HFT-F

5 MP Full Time Color Camera



- 5 MP
- 24-hour color image
- 130 dB true WDR, 3D DNR
- 3.6 mm, 6 mm fixed focal lens
- Smart Light, up to 20 m white light distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE10HFT-F(3.6mm)

## DS-2CE12DFT-PIRX0F

2 MP PIR Siren Full Time Color Camera



- 2 MP
- 24-hour color image
- 130 dB true WDR, 3D DNR
- 3.6 mm, 6 mm fixed focal lens
- Smart Light, WL 40m
- PIR detection, strobe light alarm, alarm out/audible alarm
- Built-in siren
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE12DFT-PIRX0F(3.6mm)

## DS-2CE16D8T-(A)IT3ZF

2 MP Ultra-Low Light Bullet Camera



- 2 MP
- Ultra-low light
- 2.7- 13.5 mm varifocal lens, auto focus
- 130 dB true WDR, 3D DNR
- Smart IR, up to 60 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE16D8T-IT3ZF(2.7-13.5mm)

## DS-2CE16D8T-ITF/3F/5F

2 MP Ultra-Low Light Bullet Camera



- 2 MP
- Ultra-low light
- 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
- 130 dB true WDR, 3D DNR
- EXIR 2.0, smart IR, up to 80 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE16D8T-IT5F(3.6mm)

## DS-2CE16D9T-AIRAZH

HD1080P WDR Motorized VF EXIR Bullet Camera



- 2 Megapixel high-performance CMOS
- Analog HD output, up to 1080P resolution
- 5-50mm motorized VF lens, auto focus
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- True WDR, up to 120dB
- Up to 110m IR distance
- IP66 weatherproof

### PART NO.

DS-2CE16D9T-AIRAZH(5-50mm)

# TURBO HD CAMERAS

## DS-2CE16H0T-(A)IT3ZF 5 MP Bullet Camera



- 5 MP
- 2.7 -13.5 mm motorized vari-focal lens
- up to 40 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE16H0T-AIT3ZF(2.7-13.5mm)

## DS-2CE16H0T-IT3F 5 MP Bullet Camera



- 5 MP
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
- EXIR 2.0, smart IR, up to 40 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE16H0T-IT3F(2.8mm)

DS-2CE16H0T-IT3F(3.6mm)

DS-2CE16H0T-IT3F(6mm)

## DS-2CE16H0T-ITF 5 MP Bullet Camera



- 5 MP
- 2.8 mm, 3.6 mm, 6 mm fixed lens
- EXIR 2.0, smart IR, up to 20 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE16H0T-ITF(2.8mm)

DS-2CE16H0T-ITF(3.6mm)

## DS-2CE19H8T-(A)IT3ZF 5 MP Bullet Camera



- 5 MP
- 2.7 -13.5 mm motorized vari-focal lens
- up to 80 m IR distance
- OSD menu, 3D DNR, 130 dB true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE19H8T-AIT3ZF(2.7-13.5mm)

## DS-2CE19U7T-AIT3ZF 8 MP Bullet Camera



- 8.29 MP
- 2.7-13.5 mm motorized vari-focal lens
- up to 80 m IR distance
- OSD menu, 3D DNR, 130 dB true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE19U7T-AIT3ZF(2.7-13.5mm)

## DS-2CE56D8T-(A)VPIT3ZF 2 MP Ultra-Low Light Dome Camera



- 2 MP
- Ultra-low light
- 2.7- 13.5 mm varifocal lens, auto focus
- 130 dB true WDR, 3D DNR
- Smart IR, up to 60 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IK10
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE56D8T-AVPIT3ZF(2.7-13.5mm)

**DS-2CE56D8T-ITMF**  
2 MP Ultra-Low Light EXIR Turret Camera



- 2 MP
- Ultra-low light
- 2.8 mm, 3.6 mm, 6 mm fixed focal lens
- 130 dB true WDR, 3D DNR
- up to 30 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

**PART NO.**

DS-2CE56D8T-ITMF(2.8mm)

**DS-2CE56H0T-IT3F**  
5 MP Turret Camera



- 5 MP
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
- EXIR 2.0, smart IR, up to 40 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

**PART NO.**

DS-2CE56H0T-IT3F(2.8mm)

DS-2CE56H0T-IT3F(3.6mm)

DS-2CE56H0T-IT3F(6mm)

**DS-2CE56H0T-ITMF**  
5 MP Turret Camera



- 5 MP
- 2.8 mm, 3.6 mm, 6 mm fixed lens
- EXIR 2.0, smart IR, up to 20 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

**PART NO.**

DS-2CE56H0T-ITMF(2.8mm)

DS-2CE56H0T-ITMF(3.6mm)

**DS-2CE56H0T-VPIT3ZF**  
5 MP Dome Camera



- 5 MP
- 2.7-13.5 mm motorized vari-focal lens
- EXIR 2.0, smart IR, up to 40 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67, IK10

**PART NO.**

DS-2CE56H0T-VPIT3ZF(2.7-13.5mm)

**DS-2CE59H8T-AVPIT3ZF**  
5 MP Ultra-Low Light Camera



- 5 MP
- Auto focus
- 2.7 - 13.5 mm motorized varifocal lens
- EXIR 2.0, smart IR, up to 60 m IR distance
- OSD menu, 3D DNR, 130 dB true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67, IK10

**PART NO.**

DS-2CE59H8T-AVPIT3ZF(2.7-13.5mm)

**DS-2CE59U7T-AVPIT3ZF**  
8 MP Dome Camera



- 8.29 MP
- 2.7- 13.5 mm motorized vari-focal lens
- up to 60 m IR distance
- OSD menu, 3D DNR, 130 dB true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67, IK10
- Up the coax (HIKVISION-C)

**PART NO.**

DS-2CE59U7T-AVPIT3ZF(2.7-13.5mm)

# TURBO HD CAMERAS

## DS-2CE5AH0T-(A)VPIT3ZF 5 MP Dome Camera



- 5 MP
- 2.7 -13.5 mm motorized vari-focal lens
- up to 40 m IR distance
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67, IK10
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE5AH0T-VPIT3ZF(2.7-13.5mm)

## DS-2CE72DFT-F 2 MP Full Time Color Turret Camera



- 2 MP
- Full time color
- 3.6 mm, 6 mm fixed lens
- Up to 20 m white light distance
- true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE72DFT-F(3.6mm)

## DS-2CE72DFT-PIRX0F 2 MP PIR Siren Full Time Color Camera



- 2 MP
- 24-hour color image
- 130 dB true WDR, 3D DNR
- 3.6 mm, 6 mm fixed focal lens
- Smart Light, WL20m
- PIR detection, strobe light alarm, alarm out/audible alarm
- Built-in siren
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE72DFT-PIRX0F(3.6mm)

## DS-2CE72HFT-F 5 MP Full Time Color Camera



- 5 MP
- 24-hour color image
- 130 dB true WDR, 3D DNR
- 3.6 mm, 6 mm fixed focal lens
- Smart Light, up to 20 m white light distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE72HFT-F(3.6mm)

## DS-2CE79H8T-AIT3ZF 5 MP Turret Camera



- 5 MP
- Auto focus
- 2.7 -13.5 mm motorized vari-focal lens
- EXIR 2.0, smart IR, up to 60 m IR distance
- OSD menu, 3D DNR, 130 dB true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

### PART NO.

DS-2CE79H8T-AIT3ZF(2.7-13.5mm)

## DS-2CE79U7T-IT3ZF 8 MP Turret Camera



- 8.29 MP
- 2.7-13.5 mm motorized vari-focal lens
- up to 60 m IR distance
- 130 dB true WDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67
- Up the coax (HIKVISION-C)

### PART NO.

DS-2CE79U7T-IT3ZF(2.7-13.5mm)

**DS-2DE2A204IW-DE3**  
2MP 4× IR Network PTZ Camera



- Up to 2MP resolution
- Min. illumination:0.005 Lux
- 4× optical zoom
- 120 dB WDR
- 12 VDC & PoE
- Up to 20 m IR distance
- H.265+/H.265

**PART NO.**

DS-2DE2A204IW-DE3

**DS-2DE2A404IW-DE3**  
4MP 4× IR Network PTZ Camera



- Up to 4MP resolution
- Min. illumination:0.005 Lux
- 4× optical zoom
- 120 dB WDR
- 12 VDC & PoE
- Up to 20 m IR distance
- H.265+/H.265

**PART NO.**

DS-2DE2A404IW-DE3

**DS-2DE4225IW-DE(D)**  
2 MP 25× Network IR Speed Dome



- Up to 2MP resolution
- Min. illumination:0.005 Lux
- 25× optical zoom
- 120dB WDR
- Up to 100 m IR distance
- 12 VDC & PoE+ (802.3at, class4)
- H.265+/H.265

**PART NO.**

DS-2DE4225IW-DE

**DS-2DE4425IW-DE(D)**  
4MP 25× Network IR Speed Dome



- Up to 4MP resolution
- Min. illumination:0.005 Lux
- 15× optical zoom
- 120dB WDR
- Up to 100 m IR distance
- 12 VDC & PoE+ (802.3 at, class4)
- H.265+/H.265

**PART NO.**

DS-2DE4425IW-DE(D)

**DS-2DE4A225IW-DE(B)**  
2 MP 25× Network IR PTZ Camera



- Up to 2MP resolution
- Min. illumination: 0.005 Lux
- 25× optical zoom
- 120dB WDR
- Up to 50 m IR distance
- Auto-tracking
- 12 VDC & PoE+ (802.3at, class4)
- H.265+/H.265

**PART NO.**

DS-2DE4A225IW-DE(B)

**DS-2DE5425IW-AE(B)**  
4MP 25× Network IR Speed Dome



- Up to 4MP resolution
- Min. illumination:0.005 Lux
- 25× optical zoom
- 120dB WDR
- Up to 150 m IR distance
- Auto-tracking
- 24 VAC & Hi-PoE
- H.265+/H.265

**PART NO.**

DS-2DE5425IW-AE(B)

# IP PTZ CAMERAS

## DS-2DE7232IW-AE(B)

2MP 32× Network IR Speed Dome



- Up to 2MP resolution
- Min. illumination: 0.005 Lux
- 32× optical zoom
- 120dB WDR
- Up to 150 m IR distance
- Auto-tracking
- 24 VAC & Hi-PoE
- H.265+/H.265

### PART NO.

DS-2DE7232IW-AE(B)

# TURBO HD PTZ CAMERAS

## DS-2AE4225TI-D(D)

2 MP IR Turbo 4-Inch Speed Dome



- 1/2.8" HD progressive scan CMOS
- 1920 × 1080 resolution
- 25× optical zoom
- 120 dB true WDR (Wide Dynamic Range)
- Up to 100 m IR distance
- 3D intelligent positioning
- Switchable TVI/AHD/CVI/CVBS video

DS-2AE4225TI-D(D)

## DS-2AE5232T-A

2 MP Turbo 5-Inch Speed Dome



- 2MP
- 32× optical zoom
- DWDR (Digital Wide Dynamic Range)
- 3D intelligent positioning
- Switchable Turbo HD and CVBS outputs

### PART NO.

DS-2AE5232T-A

## DS-2AE7232TI-A(C)

2 MP IR Turbo 7-Inch Speed Dome



- 1/2.8" HD progressive scan CMOS
- 1920 × 1080 resolution
- 32× optical zoom, 16× digital zoom
- 120 dB true WDR (Wide Dynamic Range)
- Up to 150 m IR distance
- 3D intelligent positioning
- Switchable TVI/AHD/CVI/CVBS video output

### PART NO.

DS-2AE7232TI-A(C)



## DS-2TD2136T-10

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncooled Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD < 40mk (@25°C,F#=1.0),
- Thermal 10 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to 550 °C (-4 °C to 1022 °F), accuracy Max ( $\pm 2$  °C,  $\pm 2\%$ ),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 36° × 27°

### PART NO.

DS-2TD2136T-10

## DS-2TD2136T-15

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncooled Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD < 40mk (@25°C,F#=1.0),
- Thermal 15 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to 550 °C (-4 °C to 1022 °F), accuracy Max ( $\pm 2$  °C,  $\pm 2\%$ ),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 24.55° × 18.54°

### PART NO.

DS-2TD2136T-15

## DS-2TD2136T-25

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncooled Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD < 40mk (@25°C,F#=1.0),
- Thermal 25 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to 550 °C (-4 °C to 1022 °F), accuracy Max ( $\pm 2$  °C,  $\pm 2\%$ ),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 14.88° × 11.19°

### PART NO.

DS-2TD2136T-25

## DS-2TD2137-10/V1

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncooled Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD less than 35mk (@25°C,F#=1.0),
- Thermal 10 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to +150 °C (-4 °F to +302°F), accuracy  $\pm 8$  °C ( $\pm 14.4$  °F),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 36° × 27° (H × V)

### PART NO.

DS-2TD2137-10/V1

## DS-2TD2137-15/V1

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncooled Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD less than 35mk (@25°C,F#=1.0),
- Thermal 15 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to +150 °C (-4 °F to +302°F), accuracy  $\pm 8$  °C ( $\pm 14.4$  °F),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 24.55° × 18.54° (H × V)

### PART NO.

DS-2TD2137-15/V1

## DS-2TD2137-25/V1

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncooled Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD less than 35mk (@25°C,F#=1.0),
- Thermal 25 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8 VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to +150 °C (-4 °F to +302°F), accuracy  $\pm 8$  °C ( $\pm 14.4$  °F),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 14.88° × 11.19° (H × V)

### PART NO.

DS-2TD2137-25/V1

# THERMAL SECURITY

---

## DS-2TD2137-35/V1

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncoldded Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD less than 35mk (@25°C,F#=1.0),
- Thermal 35 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to +150 °C (-4 °F to +302°F), accuracy  $\pm 8$  °C ( $\pm 14.4$  °F),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 10.66°  $\times$  8.002° (H  $\times$  V)

---

### PART NO.

DS-2TD2137-35/V1

---

## DS-2TD2137-7/V1

Thermal Network Bullet Camera



- 384\*288 resolution, Vanadium Oxide Uncoldded Focal Plane Arrays,
- 17  $\mu\text{m}$  detector, 8  $\mu\text{m}$  to 14  $\mu\text{m}$ ,
- NETD less than 35mk (@25°C,F#=1.0),
- Thermal 7 mm lens,
- 4 VCA rule types (Line Crossing, Intrusion, Region Entrance, and Region Exiting), up to 8VCA rules,
- 3 temperature measurement rule types, 21 rules (10 points, 10 areas, and 1 line), -20 °C to +150 °C (-4 °F to +302°F), accuracy  $\pm 8$  °C ( $\pm 14.4$  °F),
- Dynamic fire detection up to 10 fire points detectable,
- FOV 60°  $\times$  43.8° (H  $\times$  V)

---

### PART NO.

DS-2TD2137-7/V1

## DS-2TP23-10VM/W

Handheld Thermography Camera



- Uncooled Focal Plane Arrays, 384\*288,
- 17 $\mu$ m, 8 $\mu$ m to 14 $\mu$ m, NETD< 40mk (@ 25 °C, F#=1.0),
- 10mm (manual focus) thermal lens,
- FOV 37.5° × 28.5° ,
- monitor 640 × 480 resolution 3.5" LCD touch display, 7 palettes,
- Thermal 1x, 2x and 4x digital zoom, image fusion and picture in picture,
- -20 °C to 550 °C [-4 °F to 1022 °F], accuracy Max ( $\pm 2$  °C,  $\pm 2\%$ ),
- Rules Max. Temperature; Min. Temperature; Center Temperature; Custom Point/Line/Area Thermometry,
- Support laser light,
- Built in memory module 64GB.

### PART NO.

DS-2TP23-10VM/W

## DS-2TP31-03AUF

Handheld Thermography Camera



- Uncooled Focal Plane Arrays,
- 160\*120, 17 $\mu$ m, 8 $\mu$ m to 14 $\mu$ m,
- NETD< 40mk (@ 25 °C, F#=1.0),
- $\geq 3.1$  mm thermal lens, FOV 37.2° × 50° ,
- -20 °C to 550 °C [-4 °F to 1022 °F], accuracy Max ( $\pm 2$  °C,  $\pm 2\%$ ), 3 thermometry points: Max. Temperature; Min. Temperature; Center Temperature;
- Support laser light, Replaceable memory card (default 8G, support up to 128G storage)

### PART NO.

DS-2TP31-03AUF

# COMMERCIAL VISION

## DS-2TS03-25UF/W

Handheld Observational Thermal Monocular



- 384 × 288 resolution, Uncooled Focal Plane Arrays,
- High sensitivity detector NETD 35mk,
- 25mm focal length,
- Black white and red hot, support wifi, with 16GB Storage,
- 1024 × 768 resolution 0.39-inch OLED display,
- 2 times digital zoom, support picture snapshot and video,
- Support GPS.
- Up to five hours continuous running (with GPS function and Wi-Fi hot spot function off)

### PART NO.

DS-2TS03-25UF/W

## DS-2TS03-35UF/W

Handheld Observational Thermal Monocular



- 384 × 288 resolution, Uncooled Focal Plane Arrays,
- High sensitivity detector NETD 35mk,
- 35mm focal length, manual focus
- Black white and red hot, support wifi, with 16GB Storage,
- 1024 × 768 resolution 0.39-inch OLED display,
- 2 times digital zoom, support picture snapshot and video,
- Support GPS.
- Up to five hours continuous running (with GPS function and Wi-Fi hot spot function off)

### PART NO.

DS-2TS03-35UF/W

# NETWORK VIDEO RECORDERS

## DS-7600NI-K1/4P(Ban) K1/4P SERIES NVR



- Dual-OS design
- ANR technology
- H.265/H.264/H.264+ video formats
- 4 IP cameras can be connected
- Recording at up to 8 MP resolution
- Supports live view, storage, and playback of the connected camera at up to 8 MP resolution
- HDMI Video output at up to 4K (3840 × 2160) resolution
- 1 SATA interfaces
- 4 independent PoE network interfaces are provided

### PART NO.

DS-7604NI-K1/4P

## DS-7604NI-K1(B) K1 SERIES NVR



- Up to 4 IP cameras connect
- H.265+
- Recording up to 8 MP resolution
- 1 SATA interface for HDD
- 4-ch 1080p synchronous playback

### PART NO.

DS-7604NI-K1(B)

## DS-7608NI-I2/8P P SERIES NVR



- Up to 8-ch 12 MP IP cameras connect
- H.265+
- Recording at up to 12MP resolution
- 2 SATA interfaces for HDD
- 8-ch 1080p synchronous playback
- POS function
- 8 PoE

### PART NO.

DS-7608NI-I2/8P

## DS-7608NI-K2 K2 SERIES NVR



- Up to 8 IP cameras connect
- H.265+
- Recording up to 8 MP resolution
- 8-ch 1080p synchronous playback
- 2 SATA interfaces for HDD

### PART NO.

DS-7608NI-K2

## DS-7608NI-K2/8P P SERIES NVR



- Up to 8 IP cameras connect
- H.265+
- Recording up to 8 MP resolution
- 8-ch 1080p synchronous playback
- 2 SATA interfaces for HDD
- 8 PoE

### PART NO.

DS-7608NI-K2/8P

## DS-7616NI-I2/16P P SERIES NVR



- Up to 16-ch 12 MP IP cameras connect
- H.265+
- Recording at up to 12MP resolution
- 2 SATA interfaces for HDD
- 16-ch 1080p synchronous playback
- POS function
- 16 PoE

### PART NO.

DS-7616NI-I2/16P

# NETWORK VIDEO RECORDERS

## DS-7616NI-K2 K2 SERIES NVR



- Up to 16 IP cameras connect
- H.265+
- Recording up to 8 MP resolution
- 8-ch 1080p synchronous playback
- 2 SATA interfaces for HDD

### PART NO.

DS-7616NI-K2

## DS-7616NI-K2/16P P SERIES NVR



- Up to 16 IP cameras connect
- H.265+
- Recording up to 8 MP resolution
- 8-ch 1080p synchronous playback
- 2 SATA interfaces for HDD
- 16 PoE

### PART NO.

DS-7616NI-K2/16P

## iDS-7716NXI-I4/16P/8S DeepinMind SERIES NVR



- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- H.265+ compression
- Recording at up to 12MP
- HDMI Video output at up to 4K (3840 × 2160) resolution
- Up to 4 SATA interfaces for HDD
- 12-ch synchronous playback at up to 1080p resolution

### PART NO.

iDS-7716NXI-I4/16P/8S

## iDS-7716NXI-I4/8S DeepinMind SERIES NVR



- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected
- Full channel IP cameras connection
- Connectable to the third-party network cameras
- H.265+ compression
- Full channel recording at up to 12MP resolution
- HDMI Video output at up to 4K (3840 × 2160) resolution
- Up to 4 SATA interfaces for HDD connection
- 12-ch synchronous playback at up to 1080p resolution
- POS information overlay on live view and playback
- POS triggered recording and alarm

### PART NO.

iDS-7716NXI-I4/8S

# DVRS

## DS-7200HQHI-K1(/A)(B) K1 SERIES TURBO HD DVR



- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 2-ch 4 MP IP cameras input
- Long distance transmission
- H.265+/H.265/H.264+/H.264 encoding
- Connectable to H.265+/H.265/H.264+/H.264 IP cameras
- Up to 4MP Lite resolution for recording
- 1 SATA interface (up to 6 TB capacity per HDD)
- 4/8/16-ch synchronous playback

### PART NO.

DS-7204HQHI-K1/A(B)

## DS-7200HQHI-K2(/A) K2 SERIES TURBO HD DVR



- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 2-ch 4 MP IP cameras input
- H.265+encoding
- Up to 4MP Lite resolution for recording
- 2HDD (up to 6 TB per HDD)
- 8/16-ch synchronous playback

### PART NO.

DS-7208HQHI-K2/A

DS-7216HQHI-K2/A

## DS-7200HTHI-K1 K1 SERIES TURBO HD DVR



- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 2/4-ch 8 MP IP cameras input
- 8 MP HDTV video input and live view
- H.265+ encoding
- Recording at up to 8 MP resolution
- HDMI output at up to 4K
- Separate CVBS output
- 1/2 SATA interface

### PART NO.

DS-7204HTHI-K1

## DS-7200HTHI-K2 K2 SERIES TURBO HD DVR



- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 2/4-ch 8 MP IP cameras input
- 8 MP HDTV video input and live view
- H.265+/H.265/H.264+/H.264 encoding
- Connectable to H.265+/H.265/H.264+/H.264 IP cameras
- Recording at up to 8 MP resolution
- HDMI output at up to 4K (3840 × 2160) resolution
- Separate CVBS output
- 1/2 SATA interface (up to 8 TB capacity per HDD)

### PART NO.

DS-7204HTHI-K2

DS-7208HTHI-K2

## DS-7200HUHI-K1 K1 SERIES TURBO HD DVR



- HDTV/HDCVI/AHD/CVBS signal input
- Up to 2-ch 6 MP IPC input
- 5 MP/4 MP HDTV video input and live view
- H.265+encoding
- Full channel recording at up to 5 MP resolution
- 1 SATA interface (up to 8 TB capacity per HDD)
- 4/8-ch synchronous playback

### PART NO.

DS-7204HUHI-K1

DS-7208HUHI-K1

## DS-7200HUHI-K1/P P SERIES TURBO HD DVR



- Self-adaptive normal camera and Hikvision PoC camera connection
- Up to 2-ch 6 MP IP cameras input
- 5 MP/4 MP HDTV video input and live view
- H.265+ encoding
- 1 SATA interface (up to 8 TB )
- 4-ch synchronous playback

### PART NO.

DS-7204HUHI-K1/P

**DS-7200HUHI-K2**  
K2 SERIES TURBO HD DVR



- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 2-ch 6 MP IP cameras input
- 5 MP/4 MP HDTV video input and live view
- Long distance transmission
- H.265+/H.265/H.264+/H.264 encoding
- Full channel recording at up to 5 MP resolution
- 2 SATA interface (up to 8 TB capacity per HDD)
- 4-ch synchronous playback

**PART NO.**

DS-7204HUHI-K2

DS-7208HUHI-K2

DS-7216HUHI-K2

**DS-7200HUHI-K2/P**  
P SERIES TURBO HD DVR



- Self-adaptive normal camera and Hikvision PoC camera connection
- Up to 2-ch 6 MP IP cameras input
- 8MP/5 MP/4 MP HDTV video input and live view
- H.265+encoding
- 2 SATA interfaces (up to 8 TB )
- 8-ch synchronous playback

**PART NO.**

DS-7208HUHI-K2/P

**iDS-7200HQHI-K1/S**  
S SERIES TURBO ACUSENSE DVR



- Filter false alarm
- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 6 MP IP cameras input
- H.265 Pro+ encoding
- Enabled
- Full channel recording at up to 4 MP lite resolution
- Simultaneous HDMI/VGA output and Separate CVBS output
- 1 SATA interface
- 4/8/16-ch synchronous playback

**PART NO.**

iDS-7208HQHI-K1/4S

**iDS-7200HUHI-K1/4S**  
4S SERIES TURBO ACUSENSE DVR



- Filter false alarm
- Self-adaptive HDTV/HDCVI/AHD/CVBS signal input
- Up to 8 MP IP cameras input
- H.265 Pro+ encoding
- Full channel recording at up to 5 MP resolution
- Simultaneous HDMI/VGA output and Separate CVBS output
- 1 SATA interface
- 4/8-ch synchronous playback

**PART NO.**

iDS-7208HUHI-K1/4S

# CONTROLLER

## DS-K2601

Single-Door Access Controller



- Up to 2 RS-485 and 2 Wiegand Card and Fingerprint Readers
- Inputs: 4 Supervised Alarm Inputs, 1 Door Contact, 1 Exit Button, 2 Case Alarm Inputs, 1 Box Tamper
- Outputs: 1 Lock Relay, 1 Alarm Relay
- 100,000 Cards 300,000 Access Control Events
- Support Battery Backup

**PART NO.**

DS-K2601

## DS-K2602

Double-Door Access Controller



- Up to 4 RS-485 and 4 Wiegand Card and Fingerprint Readers
- Inputs: 4 Supervised Alarm Inputs, 2 Door Contact, 2 Exit Button, 4 Case Alarm Inputs, 1 Box Tamper
- Outputs: 2 Lock Relay, 2 Alarm Relay
- 100,000 Cards ,300,000 Access Control Events
- Support Battery Backup

**PART NO.**

DS-K2602

## DS-K2604

Four-Door Access Controller



- TCP/IP, RS-485 Uplink Interface
- Up to 8 RS-485 and 4 Wiegand Card and Fingerprint Readers
- Inputs: 4 Supervised Alarm Inputs, 4 Door Contact, 4 Exit Button, 8 Case Alarm Inputs, 1 Box Tamper
- Outputs: 4 Lock Relay, 4 Alarm Relay
- Uplink Interface: TCP/IP and RS-485 Interface
- 100,000 Cards
- 300,000 Access Control Events
- Battery Backup
- Fire Alarm Relay
- Advanced Access Control Functions: Controller Based Global Anti-pass back, Multi-Door Interlocking, Multiple Authentication, Controller Based Linkages

**PART NO.**

DS-K2604

## DS-K2801

Entry Level Single-Door Access Controller



- Up to 2 Wiegand Card Readers
- 10,000 cards and 50,000 events buffer
- Reader Interfaces: 2 Wiegand readers
- Inputs: 1 Door Contact, 1 Exit Button, 1 Case Alarm Input,
- Outputs: 1 Lock Relay, 1 Alarm Relay

**PART NO.**

DS-K2801

## DS-K2802

Entry Level Double-Door Access Controller



- Up to 4 Wiegand Card Readers
- 10,000 cards and 50,000 events buffer
- Reader Interfaces: 2 Wiegand readers
- Inputs: 1 Door Contact, 1 Exit Button, 1 Case Alarm Input,
- Outputs: 1 Lock Relay, 1 Alarm Relay

**PART NO.**

DS-K2802

## DS-K2804

Entry Level Four-Door Access Controller



- Up to 4 Wiegand (Entry) Card Readers
- 10,000 cards and 50,000 events buffer
- Reader Interfaces: 2 Wiegand readers
- Inputs: 1 Door Contact, 1 Exit Button , 1 Case Alarm Input,
- Outputs: 1 Lock Relay, 1 Alarm Relay

**PART NO.**

DS-K2804



---

## DS-K1T804MF

IP Fingerprint Access Control Terminal



- Built-in Mifare Card reading module
- 2.4 inch LCD – TFT Screen
- 18 Keys Keyboard and doorbell
- 3000 fingerprints , 3000 cards,100,000 access control events
- Uplink Communication: TCP/IP, Wi-Fi
- Supports local Time & Attendance function, generating reports automatically

---

### PART NO.

DS-K1T804MF

## READERS & KEYPADS

---

## DS-K1104MK

Vandal-proof Card Reader



- Mifare 13.65 frequency
- Keypad with backlight
- RS-485 and Wiegand interface
- IK10 Vandal proof, Zinc-Alloy
- Tamper-proof

---

### PART NO.

DS-K1104MK

---

## DS-K1107MK

Card Reader



- EM 125Khz frequency
- Keypad with backlight
- RS-485 and Wiegand interface
- Tamper-proof
- 115mm × 44mm × 22mm

---

### PART NO.

DS-K1107MK

# VIDEO INTERCOM KIT

## DS-KIS602

IP Video Intercom Kit



- DS-KD8003-IME1/Surface x1;
- DS-KH6320-WTE1 x1;
- 4 port standard PoE switch x1;
- 16GB TF card x1;
- PLUG & PLAY

### PART NO.

DS-KIS602

## DS-KIS701-B-D

2-Wire IP Kit



- DS-KV8103-IME2 x1 ; DS-KH8340-TCE2/EU-B x1; DS-KAD709 x1;
- DIN RAIL power supply for DS-KAD709

### PART NO.

DS-KIS701-B-D

## DS-KIS701-W-D

2-Wire IP Kit



- DS-KV8103-IME2 x1 ; DS-KH8340-TCE2/EU-W x1; DS-KAD709 x1;
- DIN RAIL power supply for DS-KAD709

### PART NO.

DS-KIS701-W-D

**DS-KD8003-IME1/EU**  
Camera module



- CMOS 2MP HD Colorful 180°Fish eye Camera,
- 1 Call Button,
- 2 relays for door lock control
- Module connection with RS-485 , 4-ch alarm input
- IP65, 12 VDC or standard POE

**PART NO.**

DS-KD8003-IME1/EU

**DS-KD8003-IME1/Flush/EU**  
Camera module



- DS-KD8003-IME1 with its flush mouting accessories. IP65 (DS-KD8003-IME1+DS-KD-ACF1)

**PART NO.**

DS-KD8003-IME1/Flush/EU

**DS-KD8003-IME1/Surface/EU**  
Camera module



- DS-KD8003-IME1 with its surface mouting accessories. IP65 (DS-KD8003-IME1+DS-KD-ACW1)

**PART NO.**

DS-KD8003-IME1/Surface/EU

**DS-KD-DIS**  
Display module



- Module connection with RS-485 , IP65,
- Dial number display, pin code unlock,
- Contact list display,
- Powered by other module

**PART NO.**

DS-KD-DIS

**DS-KD-KK**  
Nametag module



- Nametag unit , needs accessories.
- 6 call buttons,
- Module connection with RS-485 , IP65

**PART NO.**

DS-KD-KK

**DS-KD-KP**  
Control panel module



- Module connection with RS-485 , IP65,
- Backlight compensation,
- Powered by other module,

**PART NO.**

DS-KD-KP

**DS-KD-M**  
Mifare card reader module



- Supports unlock the door via wiping cards
- Backlight compensation
- Easy to and extend

**PART NO.**

DS-KD-M

# IP INDOOR STATIONS

## DS-KH6320-WTE1/EU 2nd Generation IP Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 1024 \* 600;
- standard PoE/ 12 VDC.
- Support TF card, max 32G
- 8-ch alarm input , 2xalarm output, 1x485

### PART NO.

DS-KH6320-WTE1 (Europe BV)

## DS-KH8350-WTE1/EU 2nd Generation IP Indoor Station



- Reddot award 2017 winner
- 7-inch Colorful TFT LCD, Metal panel display resolution: 1024 \* 600;
- 10/100Mbps Ethernet, Wi-Fi 802.11b/g/n;
- standard PoE/ 12 VDC.
- Support TF card, max 32G
- 8-ch alarm input , 2xalarm output, 1x485

### PART NO.

DS-KH8350-WTE1 (Europe BV)

## DS-KH8520-WTE1/EU 2nd Generation IP Indoor Station



- 10-inch Colorful TFT LCD, display resolution: 1024 \* 600;
- standard PoE/ 12 VDC.
- Support TF card, max 32G
- 8-ch alarm input, 2xalarm output, 1x485

### PART NO.

DS-KH8520-WTE1 (Europe BV)

# HIKVISION INTRUSION ALARM

## DS-PR1-60 Security Radar



- Detection range: 60m
- Detection angle: 100°
- Up to 32 targets dection
- Up to 4 PTZ cameras linkage
- IP67

### PART NO.

DS-PR1-60

## DS-PWA32-NGT

868MHz Wireless control Panel Kits with IC Cards (GPRS Version)



- Card Reading
- GPRS

### PART NO.

DS-PWA32-NGT

## DS-PWA32-NK

868MHz Wireless Control Panel Kits with keyfob



- Keyfob

### PART NO.

DS-PWA32-NK

## DS-PWA32-NKG

868MHz Wireless Control Panel Kits with keyfob (GPRS Version)



- Keyfob
- GPRS

### PART NO.

DS-PWA32-NKG

## DS-PWA32-NST

868MHz Wireless control Panel Kits with IC Cards (3G/4G Version)



- Card Reading
- 3/4G

### PART NO.

DS-PWA32-NST

## HIKVISION WIRELESS DUAL-TECH DETECTOR

## DS-PD2-D10P-W

Wireless Dual-Tech Detector



- Two way wireless - Pet Immunity - Tamper protection: front, rear and bracket - Bluewave Technology - Digital Temperature Compensation - Automatic Sensitivity - Singnal Strength Indicators(SSl) - Ceiling/Wall bracket include - 3 Microwave Frequencies - Ceiling/Wall bracket include

### PART NO.

DS-PD2-D10P-W

## DS-PD2-D12-W

Wireless Dual-Tech Detector



- Two way wireless - Digital Temperature Compensation - Automatic Sensitivity - Singnal Strength Indicators(SSl) - 3 Microwave Frequencies

### PART NO.

DS-PD2-D12-W

# DISPLAYS

## DS-D5032QE

32" 1080P Monitor



- 31.5" 1080P, HDMI/VGA input, 5W\*2 speaker, view angle:178°/178°, 300cd/m<sup>2</sup>, plastic casing, ERP level A, VESA, base bracket included, High reliable components for 7 x 24 working, 3D comb filter, 3D De-interlace, 3D noise reduction

### PART NO.

DS-D5032QE

## DS-D5043QE

43" 1080P Monitor



- 43" 1080P, HDMI/VGA input, view angle:178°/178°, 360cd/m<sup>2</sup>, Build-in speaker, Audio 5W\*2, plastic casing, VESA, base bracket included, High reliable components for 7 x 24 working, 3D comb filter, 3D De-interlace, 3D noise reduction

### PART NO.

DS-D5043QE

## DS-D5050UC

50" 4k Monitor



- 50" 4k, HDMI/VGA/DVI/DP input, USB3.0 x2 (B/C \*1), USB2.0 x2, build-in speaker, view angle:178°/178°, plastic casing, VESA, High reliable components for 7 x 18 working, 3D comb filter, 3D De-interlace, 3D noise reduction

### PART NO.

DS-D5050UC

## DS-D5055UC

55" 4k Display



- 55" 4K, HDMI\*2, VGA\*1, USB2.0, USB3.0, build-in speaker, view angle 178°/178°, plastic casing, VESA, High reliable components for 7 x 24 working, 3D comb filter, 3D De-interlace, 3D noise reduction

### PART NO.

DS-D5055UC

## DS-D5055UL-B

55" 4k Display



- 55" 4K, 2\*HDMI/VGA/DVI/BNC input, build-in speaker, view angle:178°/178°, metal casing, High reliable components for 7 x 24 working, 3D comb filter, 3D De-interlace, 3D noise reduction

### PART NO.

DS-D5055UL-B

## DS-3E0310HP-E

10-ports 100Mbps Unmanaged PoE Switch with 2 uplink port



- L2, Unmanaged, 8 10/100M RJ45 PoE ports, 2 Gigabit RJ45 uplink ports, 802.3af/at/bt, port 1 support HiPoE 60w, PoE power budget 110W, max. 250m long distance transmission, 6KV surgy protection

### PART NO.

DS-3E0310HP-E

## DS-3E0510P-E

Gigabit POE switch with 8 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port



- L2, Unmanaged, 8 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, 802.3af/at, PoE power budget 110w

### PART NO.

DS-3E0510P-E

## DS-3E0518P-E

Gigabit POE switch with 16 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port



- L2, Unmanaged, 16 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, 802.3af/at, PoE power budget 230w

### PART NO.

DS-3E0518P-E

# 2019

## Q3 CORE PRODUCT QUICK GUIDE



### Hikvision Headquarters

No.555 Qianmo Road  
310052 Hangzhou  
China  
T +86 571 88075998  
sales@hikvision.com

### Hikvision Europe

Dirk Storklaan 3  
2132 PX Hoofddorp  
The Netherlands  
T +31 23 5542770  
info.eu@hikvision.com

### Hikvision France

6 rue Paul Cézanne,  
93360 Neuilly-Plaisance  
France  
T +33 (0)1 85330450  
info.fr@hikvision.com

### Hikvision Italy

Via Abruzzo 12  
Z.I. San Giacomo  
31029 Vittorio Veneto TV  
Italy  
T +39 0438 6902  
info.it@hikvision.com

### Hikvision Poland

The Park, Office Building A  
Krakowiaków 50  
02-255 Warsaw, Poland  
T +48 22 4600150  
info.pl@hikvision.com

### Hikvision Spain

Calle de Almazara 9  
28760 Tres Cantos  
Madrid, Spain  
T +34 91 7371655  
info.es@hikvision.com

### Hikvision Czech

BETA Building, Vyskocilova  
1481/4, Prague 4  
Czech Republic  
T +42 29 6182640  
info.cz@hikvision.com

### Hikvision Germany

Flughafenstr. 21  
63263 Neu-Isenburg  
Zeppelinheim, Germany  
T +49 69 401507290  
sales.dach@hikvision.com